



## PAR-36 & PAR-36E Strobe Heads

The model PAR-36 and PAR-36E remote strobe heads are designed to be used with Tomar's strobe power supplies. Tomar PAR lighthouse family of remote strobeheads feature a sealed beam strobe lamp with a Lexan lens. Tomar's PAR-36E EXTENDED LENS remote strobeheads feature Tomar's SIDE OPTICS that create a wide beam spread pattern of light, visible from the front and both sides. The PAR-36 and PAR-36E are available with a choice of black rubber (shown in above picture) or stainless steel shells.

## RECT-34 & 37 Strobe Heads

The model RECT-37 and RECT-34 series sealed beam lamps are 100% watertight and feature a chrome coated reflector. They are molded from Lexan and designed to fit all popular utility, large mobile equipment and trucks. The RECT-37 & RECT-34 are furnished with a drill template, gasket, and mounting hardware; and can be used with all Tomar power supplies.

### ORDERING INFORMATION

- PAR-36B-AMBER** Amber sealed beam strobehead, rubber shell, 15' cable
- PAR-36EB-AMBER** Amber sealed beam, extended lens, rubber shell, 15' cable
- PAR-36ES-AMBER** Amber sealed beam, extended lens, SS Shell, 15' cable
- PAR-36S-AMBER** Amber sealed beam strobehead, SS Shell, 15' cable
- PAR-36-SS** PAR-36 stainless steel shell
- UBKT** Universal SS bracket for PAR-36 or PAR-36E lighthoods
- PAR-36B-S** PAR-36 black rubber shell
- 15C** 15' cable

### ORDERING INFORMATION

- RECT-37S-AMBER** Amber remote 3" X 7" rectangular strobe lamp
- RECT-34S-AMBER** Amber remote 3" X 4" rectangular strobe lamp

### SPECIFICATIONS

**Intensity:**

**Intensity in Candelas Effective**

Power Supply	Amber	Note
<b>772P-1228</b>	2100	
<b>770P-1228</b> with 1 group on	1500	
<b>770P-1228</b> with 2 groups on	2930	*
<b>776-1228</b> with 1 group on	1550	
<b>776-1228</b> with 2 groups on	2930	*

\* Use with outside free air application only

Divide by 2 when using heads that flash simultaneously

Note: Intensity when viewing PAR-36E from side is 20% of the intensity rating to the front.

Warranty: Standard Tomar Warranty

### SPECIFICATIONS

**Intensity:**

**Intensity in Candelas Effective, based on a single head**

Power Supply	RECT-34S-AMBER	RECT-37S-AMBER
772P-1228	1040	5630
770P-1228	820	8480
776-1228	820	8480

Divide by 2 when using heads that flash simultaneously

Note: Intensity when viewing the RECT-34S from the side is 35% of the intensity rating to the front.

Warranty: Standard Tomar Warranty

**Call, fax or email for information on enclosures:  
(surface mtg., recess mtg., bumper mtg.)**

**Call: 800-227-9636**

**Fax: 800-592-4700**

**Email: sales@maxi-signal.com**